





|            |                              |                                                                 |     |              |     |              |     |               |      |      |               |      |  |
|------------|------------------------------|-----------------------------------------------------------------|-----|--------------|-----|--------------|-----|---------------|------|------|---------------|------|--|
|            | voltage                      |                                                                 |     |              |     |              |     |               |      |      |               |      |  |
|            | Overload capacity            | 125%→10min,150%→1min                                            |     |              |     |              |     |               |      |      |               |      |  |
|            | Static switch                | Automatic                                                       |     |              |     |              |     |               |      |      |               |      |  |
|            | Protection                   | UPS over current, short circuit, battery low voltage, over heat |     |              |     |              |     |               |      |      |               |      |  |
|            | Cold method                  | Compel aeration ( temperature control mode)                     |     |              |     |              |     |               |      |      |               |      |  |
|            | Noise                        | 60-65dB                                                         |     |              |     |              |     |               |      |      |               |      |  |
|            | Display                      | LED、LCD display                                                 |     |              |     |              |     |               |      |      |               |      |  |
|            | Communication port(Optional) | RS232, SNMP, dry-contact                                        |     |              |     |              |     |               |      |      |               |      |  |
|            | Alarm                        | Alarm with buzzer and indicators                                |     |              |     |              |     |               |      |      |               |      |  |
|            | Environment                  | Temperature: 0-40C Humidity: 0-90%                              |     |              |     |              |     |               |      |      |               |      |  |
| Net weight | kgs                          | 210                                                             | 258 | 350          | 400 | 480          | 900 | 1100          | 1200 | 1250 | 1380          | 1520 |  |
| Size       | L*W*H (mm)                   | 700×520×1100                                                    |     | 800×600×1200 |     | 800×600×1500 |     | 1200×900×1600 |      |      | 2000×900×1800 |      |  |